

- Above-ground buildings, 12
- Abutments, 309
- Acceleration, 76
- Accidental eccentricity, 347
- Accuracy of computations, xi
- ACI Code (Ref. 16), 383
- Active soil pressure, 308
- Adjusted design values, wood, 125
- Admixtures, 208
- Adobe, 279
- Aggregates, for concrete, 207
- Air-entraining:
 - aggregate, 208
 - cement, 208
- Air-supported structure, 35
- AISC Manual (Ref. 10), 383
- Algebraic analysis of truss, 51
- Allowable deflection, 129, 170, 221
- Allowable loads, *see* Safe Loads
- Allowable stress, for structural lumber, 124
- Allowable stress design (ASD), 2, 391
- Aluminum, 20
- American Concrete Institute (ACI), 383
- American Institute of Steel Construction (AISC), 383
- American Society for Testing and Materials (ASTM), 383
- American standard beams (S shapes or I-beams), 157
- American standard channels, 157, 476
- Amplitude of harmonic motion, 77
- Anchorage:
 - devices, 150, 378
 - of shear walls, 356, 404
- Anchor bolts, 404
- Angles, structural steel, 157, 477
 - double, 192, 201, 478
 - gage for bolts, 199
 - properties of, 477, 478
 - as steel columns, 192
 - in tension, 89
- Approximate design of indeterminate structures, 233, 455, 448, 450
- Arch, 30, 276
- Architectural:
 - considerations, 3
 - terra cotta, 280
- Areas of:
 - slab reinforcement, 219
 - steel reinforcing bars, 213
- Atterberg limits, 285
- Axial force, 57
- Balanced:
 - reinforcement in beams, 213
 - section, concrete beam, 213
- Bars, reinforcing, *see* Reinforcement, 209
- Bars and plates, steel, 157
- Base shear, seismic force, 347
- Basic wind speed, 338
- Beams, 80
 - bearing, 128,
 - bending in, 82, 84
 - buckling, 83, 87, 174
 - cantilever, 80
 - compact section, steel, 162
 - coefficients for indeterminate beams, 233
 - compact, steel, 163
 - compressive reinforcement for, 218
 - concentrated load, 82
 - concrete, 211
 - connections:
 - steel, 196
 - wood, 147
 - continuous, 445
 - deflection, 85, 128, 169
 - diagrams, typical loadings, 87
 - double-reinforced, 218
 - effective depth, concrete, 212
 - equivalent load for, 87
 - fixed end, 80
 - flexure, 59, 126, 159, 211
 - framed connections, steel, 200
 - glued laminated, wood, 119
 - indeterminate, 82, 445
 - inflection of, 85
 - internal resisting moment, 161
 - lateral buckling, 83, 87
 - lateral support for, 128
 - least-weight selection, 166
 - loading, 80
 - load-span values, steel, 173
 - moment diagram, 85
 - moment in, 84, 161
 - overhanging, 80
 - plastic hinge, 161
 - plastic moment, 161
 - reactions, 83
 - restrained, 80
 - rotational buckling, 83, 88
 - safe load tables for, steel, 171
 - shear diagram, 84
 - shear in, 83, 84, 127, 221
 - simple, 80
 - size factor for, wood, 125, 127
 - stability, 82
 - statically indeterminate, 82
 - steel, 158
 - stresses in, 66
 - support conditions, 80
 - tabular data for, 87
 - T-beams, 216
 - torsion in, 174
 - torsional buckling, 83, 88, 87
 - types of, 80
 - typical loadings, 80
 - uniformly distributed load, 81
 - web crippling, 179
 - web shear, 167
 - web tearing, 198
 - wood, 126
- Bearing pressure in soils:
 - horizontal, 282, 308
 - presumptive, 283
 - vertical, 282, 288
- Bearing walls, 23
 - brick, 264, 271
 - concrete block (CMU), 405
 - masonry, 262, 268
 - stone, 276
 - wood, 144
- Bearing of wood beams, 128
- Bending:
 - in beams:
 - concrete, 211, 242, 245
 - general, 84

- Bending: (*continued*)
 - steel, 158
 - wood, 126
- biaxial, 70
- in columns, 98
- factors, for steel columns, 194
- of reinforcement, 210
- stress, 59
- unsymmetrical, 70
- Bending moment:
 - diagrams for in beams, 85
 - formulas for, 85
 - negative, 85
 - positive, 85
 - sign of, 85
- Bents:
 - concrete, 450
 - multistory, 450, 457
 - rigid frame, 104, 450, 457
 - single span, 110
 - steel, 437
 - trussed, 437
- Biaxial bending, 70
- Bolted connections:
 - block shear, 198
 - effective net area in, 89, 199
 - framed beam connections, steel, 200
 - gage for angles, 199
 - layout of, 199
 - in steel, 196
 - tearing in, 198
 - tension stress in, 89, 199
 - in wood, 147
- Bolts:
 - edge distance for, in steel, 199
 - high-strength, 196
 - spacing in steel, 199
 - in wood, 147
 - unfinished, 198
- Box system, for lateral force, 319
- Braced frame, 319, 361, 437, 455
- Bracing of frame structures, 319
- Brick construction, 264, 271
- Buckling:
 - of beams, 128, 174
 - of columns, 94, 188
 - of web of steel beam, 179
- Building code requirements:
 - for earthquakes, 344
 - for live loads, 387
 - for wind, 339
- Building form, effects on lateral resistance, 326
- Building-ground relationships, 10
- Built-up sections:
 - in steel, 187
 - in wood, 122, 144
- Cable structures, 90
- Cantilever:
 - beam, 80
 - footing, 294
 - retaining wall, 314
 - rigid frame, 106
- Categorization of structural systems, 22
- Cement, 207
- Center:
 - of lateral resistance, 328
- shear, 68
- of stiffness, 328
- Centroid, 468
- Channels (C shape), steel, 157, 476
- Chord in horizontal diaphragm, 353, 403
- Clay, 288
- Coefficient of:
 - friction, 73
 - thermal expansion, 63
- Cohesionless soil, 286
- Cohesive soil, 286
- Cold-formed products, 180
- Collapsing soil, 290
- Collector, in horizontal diaphragm, 377
- Columns:
 - allowable loads for:
 - rectangular tied, concrete, 246
 - round tied, concrete, 247
 - square tied, concrete, 245
 - steel angles, 192
 - steel pipe, 191
 - steel tubular sections, 192
 - steel W shapes, 190
 - wood, solid, 139
 - bending factors for, 194
 - bending in, 98, 145, 192
 - brick, 275
 - buckling, 94, 188
 - built-up:
 - steel, 187
 - wood, 144
 - combined axial load and moment, 70, 145, 192, 246
 - design of:
 - concrete, 238, 242, 245, 448
 - steel, 187
 - wood, 144
 - eccentrically loaded, 70
 - effective buckling length, 95, 188
 - end conditions, 93, 187
 - Euler curve for, 94
 - footing for, 249
 - interaction, axial load plus moment, 95, 145, 192, 242
 - masonry, 230, 275
 - multistory, 243, 435
 - P-delta effect, 99
 - Pilaster, 270, 426
 - pipe, steel, 191
 - pole, 144
 - reinforced concrete, 238
 - relative slenderness of, 93, 187
 - round:
 - concrete, 247
 - wood, 143
 - slenderness of, 93, 187
 - solid, wood, 139
 - spiral, concrete, 239
 - steel:
 - angle, 192
 - pipe, 191
 - tubular, 192
 - W shape, 190
 - structural steel tubing, 192
 - stud, 144
 - tied, concrete, 239
 - in walls, 300
 - wood, 139
- Combined axial force and moment, 70, 145, 192, 242
- Combined loads, 15, 390
- Combined stress:
 - in beam, 68
 - in compression element, 70, 96
 - in footing, 96
 - in tension element, 92
- Compaction of fill, 314
- Compact section, steel W shape, 163
- Components of a force, 42
- Composite construction, 64, 120, 238
- Composition of forces, 42
- Compression:
 - in column, 93
 - reinforcement in concrete beams, 218
- Computations, xi
- Concentrated load, 80
- Concrete:
 - ACI code (Ref. 16), 383
 - admixture, 208
 - aggregate, 207
 - air-entrained, 208
 - balanced section properties, 213
 - beams, 211, 235
 - beam with compressive reinforcement, 218
 - bent, 450
 - cantilever retaining wall, 314
 - cement, 207
 - column, 238, 448
 - column footing, 249
 - composite construction, 64, 120, 238
 - cover, 242
 - creep, 208
 - curing of, 206
 - development of reinforcement, 231
 - deflection control, 221
 - flat slab structure, 237
 - flat-spanning systems, 232
 - flexural members, 211, 235
 - floor systems, 232
 - general concerns, 19, 203
 - foundations, 247, 409, 453
 - general requirements, 203
 - hook in, 230
 - masonry, 265, 267
 - materials for, 206
 - mixing, 206
 - modulus of elasticity, 208
 - precast, 206
 - reinforced, 205
 - reinforcement, 209
 - resistance factors for, 210
 - rigid frame, 374, 450
 - shape of beams, 235
 - shear in, 221
 - shrinkage, 209
 - sitecast, 215
 - slab and beam system, 232, 444
 - slab on grade, 312
 - spanning slab, 219, 233
 - specified compressive strength, f'_c , 208
 - splice in reinforcement 231
 - stirrup, 222
 - strength, 208
 - T-beam, 216
 - two-way solid slabs, 237
 - usage considerations, 203

- waffle construction, 205
- wall footing, 254
- width of beams, 215
- workability, 208
- Coefficient of thermal expansion, 63
- Connections:
 - bolted,
 - steel, 196
 - wood, 147
 - framing, 150, 200
 - nailed, 147
- Concentrated load on steel beams, 179
- Conversion factors for units, xv
- Core bracing, 433
- Cover of reinforcement, 242
- Cracked section, 97
- Creep, of concrete, 208
- Crippling of beam web, 179
- Curing of concrete, 206
- Cut:
 - and fill, 281
 - section, 40
- Dancing, 326
- Dead load of building construction, 387
- Deck:
 - concrete, 232
 - plywood, 132
 - steel, 180
 - wood plank, 118, 132
- Deep beam:
 - horizontal diaphragm as, 354
 - shear wall as, 360
- Deep foundations, 248, 288, 304
- Deflection:
 - allowable, 129, 170
 - of beams, general, 85
 - of concrete beams and slabs, 221
 - effects of, 169
 - formulas for typical beam loadings, 87
 - of steel beams, 169
 - of wood beams, 128
- Delta truss, 202
- Design of structures, 18, 391
 - computer aided, 386
 - economy, 385
 - feasibility, 2
 - integration in building, 3
 - loads, 386
 - methods, 381, 391
 - optimization of, 2
 - planning, 384
 - process, 381
 - standards and aids, 382
- Design methods, structural, 381, 391
- Designation for structural products:
 - formed sheet steel deck, 180
 - open web steel joists, 176
 - rolled steel sections, 158
 - steel joist girders, 178
- Development for reinforcement, 228
 - compression, 231
 - tension, 228
- Diagonal stress due to shear, 65
- Diaphragm:
 - chord, 353
 - with hole, 429
- horizontal, 350, 353
- vertical (shear wall), 354
- Differential settlement of foundations, 291
- Domes, 30
- Double shear, 59, 196
- Doubly reinforced beams, 218
- Downhill frame, 314
- Drift, 340
- Dual-bracing system, 369
- Ductility, 62
- Duration of load, wood, 125
- Dynamic effects, 17, 79
- Earthquake, 341, *see also* Seismic
- Eccentric bracing, 363
- Eccentric load:
 - on column, 70
 - on footing, 96
 - on lateral resisting structures, 328
- Economy, 2, 385
- Effective:
 - column length, 95, 188
 - depth of concrete beam, 212
 - net area in tension member, 89
 - width of concrete T-beam flange, 216
- Elastic behavior, 62
- Elastic limit, 62
- Elastic stress-strain response, 62
- Enclosure function of building skin, 3
- Engineered wood products, 119
- Energy, 77
- Equilibrium, 15, 42
- Equivalent:
 - static effect of dynamic load, 79
 - uniform load for deflection, 86, 174
- Expansion, thermal coefficient of, 63
- Expansive soil, 290
- Factored loads, 390
- Feasibility of structural design, 2
- Filter function of building skin, 3
- Fire safety, 1
- Fixed end beam, 80
- Flat plate, concrete, 237
- Flat slab, concrete, 237
- Flat-spanning structures, 27, 232
- Flexible structural elements, 90
- Floor-ceiling space in multistory building, 236
- Floors, general concerns, 6
- Footings:
 - closely spaced, 294, 296
 - column, 249
 - combined, 294
 - at different elevations, 296
 - differential settlement of, 291
 - moment-resistive, 96, 294
 - oblong, 294
 - for shear wall, 296
 - wall, 254
- Force:
 - analysis, 45
 - axial, 57
 - components, 42
 - composition, 42
 - equilibrium, 15, 42
 - graphical analysis of, 42, 47
 - internal, 16
 - notation for truss analysis, 45, 47
 - polygon, 44
 - properties, 41
 - resolution of, 42
 - systems, 22
- Form-scale relations, 6
- Formed sheet steel, 180
- Foundations:
 - abutment, 309
 - behavior, 288
 - column footing, 249
 - deep, 248, 288, 304
 - design, 282, 409, 453
 - differential settlement of, 291
 - downhill frame, 314
 - framed floor on grade, 314, 398
 - general considerations, 281
 - grade beam, 299, 409
 - hillside, 314
 - horizontal forces on, 283, 308
 - moment resistive, 96, 294
 - pedestal, 303
 - pier, 306
 - pile, 305
 - shallow bearing, 248, 293, 409
 - for shear wall, 296
 - wall, 254, 298, 409
- Framed floor on grade, 314, 398
- Framed structures, 22
- Framing plans for:
 - concrete, 232, 426, 444
 - steel, 407, 414, 425, 434, 438
 - wood, 400, 420
- Free-body diagram, 40
- Friction, 73
 - on soils, 308
- Fundamental period, 17, 77
- Gabled bent, 27
- Gage distance in steel angles, 199
- Geodesic dome, 36
- Glued-laminated wood products, 119
- Grade:
 - beam, 299, 409
 - of soil particle size, 284
 - steel, 155
 - of steel reinforcement, 209
 - wood, 124
- Graphical analysis:
 - of forces, 42
 - of truss, 47
- Greek letters, as symbols, xiii
- Harmonic effects, 77
- Heavy timber, 114, 418
- Hold-down anchor, 356, 404
- Hook in concrete, 230
- Horizontal:
 - anchor, 152, 379
 - diaphragm, 350, 353, 403, 429
 - soil pressure, 283, 308
 - truss bracing, 363, 416
- I-beam (S shapes), steel, 157
- I-joists, wood, 121
- Inelastic behavior, 73
- Inflated structures, 35

- Inflexion of beams, 85
- Integration of structures in building, 3
- Interaction, compression plus bending, 95, 145, 242
- Interior space division, 4
- Internal force, 16
- Interrupted shear wall, 332
- Irregular structure, for seismic load, 345
- Investigation of
 - soils, 282, 291
 - structures, 18, 39
- Joists:
 - girder, 178, 415
 - open web, steel, 176
 - wood, 130
- K-bracing, 364
- Kern, 87
- K factors for effective column length, 188
- Kinematics, 76
- Kinetic energy, 77
- Kinetics, 77
- Knee-brace, 364
- Lamella frame, 36
- Laminated veneer lumber (LVL), 120
- Lapped splice of reinforcement, 231
- Lateral:
 - buckling:
 - of beams, 87, 128
 - of columns, 93, 139, 188
 - drift, 340
 - load, 316
 - application, 317
 - design for, 401
 - due to earthquake, 316
 - due to wind, 316, 401, 412, 421, 437, 450
 - propagation in buildings, 317
 - resistance of ordinary construction, 321
 - soil pressure, 282, 308
 - support for:
 - beams, 128
 - columns, 93, 139, 166, 187
 - trusses, 104
 - unsupported length, 94, 108, 166, 187
- Lateral resistive structures, 319, 326, 433
 - box system, 319, 433
 - braced (trussed) frame, 319, 361, 437
 - collectors for, 377
 - concrete:
 - precast, 325
 - sitecast, 325
 - dancing, 326
 - dual bracing, 369
 - eccentric bracing, 363
 - externally braced frame, 319
 - horizontal diaphragm, 350, 353, 403
 - irregular form, 345
 - interaction of frames and diaphragms, 374
 - K-bracing, 364
 - light wood frames and diaphragms, 321, 354, 401
 - moment-resistive-frame, 319, 369, 450, 457
 - offset bracing, 332
 - perimeter bracing, 433, 441
 - resistance of ordinary construction, 321
 - rigid frame, 319, 369, 450, 457
 - self-stabilizing, 319
 - shear wall, 354, 404, 412, 426, 433, 442, 455
 - soft story, 327, 334
 - steel frame, 324, 433, 455
 - structural masonry, 323, 405, 426, 442
 - subdiaphragm, 332
 - three-sided building, 328
 - vertical diaphragm, 354
 - vulnerable elements, 333
 - weak story, 327, 334
 - wood frame, 321
 - X-bracing, 362
- Least-weight section, 166
- Light-gage steel elements, 180
- Light wood frame, 117, 399, 410
- Liquid limit of soil, 286
- Live load (LL),
 - for floor, 389
 - reduction, 389
 - for roof, 389
- Load:
 - building code requirements, 387
 - combinations, 15, 390
 - concentrated, 82
 - dead (DL), 387
 - dispersion, 14
 - duration, wood, 125
 - earthquake, 319, 341
 - equivalent:
 - static, 79
 - uniform, 86, 124
 - factored, 390
 - floor, live, 389
 - hydraulic pressure, 308
 - lateral, 316
 - live (LL), 388
 - periphery, 390
 - propagation in buildings, 317
 - roof, 389
 - service, 390
 - soil pressure, 283, 308
 - sources, 12, 386
 - uniformly distributed, 80
 - wind, 317, 335, 401, 412
- Load and resistance factor design (LRFD), 2, 392
- Load distribution:
 - to lateral bracing, 317
 - by peripheral method, 351
 - by relative stiffness, 351
- Load, safe:
 - column footings, 254
 - concrete columns, 246
 - nails, 149
 - open web steel joists, 177
 - plywood deck, 133, 134
 - steel beams, 173
 - steel columns, 191,
 - steel roof deck, 181
 - wall footings, 256
 - wood columns, 143
- Lumber, structural, 117
 - reference values for, 124
 - sizes and properties, 480
- Manufactured trusses, 136, 176
- Masonry:
 - adobe, 279
 - arches, 276
 - bearing walls, 268, 405
 - brick, 264, 271, 275
 - CMU, 259, 268, 405, 413, 426, 441
 - column, 270, 275
 - concrete, 265, 267, 405, 413, 426, 441
 - control joints, 266
 - dimensions of units, 265
 - form of compressive elements, 270
 - general concerns, 20
 - minimum construction, 263, 268
 - mortar, 259
 - pilaster, 270, 426
 - reinforced, 259, 263, 268, 274
 - reinforcement, 259
 - shear wall, 269, 273
 - stone, 276
 - structural, 262
 - terminology, 262
 - terra cotta, 280
 - thickness of walls, 272
 - units, 259, 265
 - unreinforced, 263
- Mast structure, 36
- Materials:
 - design considerations, 18
 - miscellaneous, 20
 - mixed, 20
 - structural, 18
 - weight of, 387
- Maxwell diagram, 47
- Measurement, units of, xiii
- Method of joints, trusses, 47
- Metric units, xiii
- Minimum width of concrete beams, 236
- Mitigation of seismic effects, 348
- Modulus:
 - of elasticity for direct stress, 62
 - section:
 - elastic, 473
 - plastic, steel, 479
- Moment:
 - in beams, 82, 84
 - diagram for a beam, 85
 - of a force, 52
 - general definition, 52
 - of inertia, 60, 469
 - internal bending moment, 59
 - negative, 85
 - overturning, 75, 340
 - positive, 85
 - restoring, 340
 - sense (sign) of, 85
 - stabilizing, 75, 340
 - torsional, 174
- Moment of inertia, 60, 469
- Moment-resisting frame, *see* Rigid frame
- Moment-resisting foundation, 96, 294
- Monopod structure, 38
- Mortar, 259
- Multilevel (multistory) buildings, 7, 243, 410, 418, 430, 455
 - ducts in floor-ceiling space, 236
 - floor-ceiling spaces, 236

- lateral bracing for, 363, 410, 433, 437, 450, 455
- Multimassed buildings, 328
- Multiple horizontal space buildings, 6
- Nailed joints, 147
- Nails, 147
- Negative:
 - bending moment, 85
 - wind pressure (suction), 338
- Net section in tension, 89
- Neutral axis, 59, 468
- Nomenclature, general, xii
- Nominal size of:
 - lumber, 117
 - rolled steel sections, 156
- Oblique cross section, 65
- One-way spanning concrete slab, 232
- Open web steel joists, 176, 405, 415, 435
- Optimization of design, 2
- Oriented strand boards (OSB), 121
- Overhanging beams, 80
- Overturning due to lateral load, 340, 356, 404
- Parallel strand lumber (PSL), 121
- Partitions, floor loads from, 390
- Passive soil pressure, 283, 308
- Paving slab, 312
- P-delta effect, 99
- Pedestal, 363
- Perimeter bracing system, 433, 440
- Period of vibration, 17
- Peripheral:
 - distribution of lateral load, 351
 - shear (punching) in concrete footing, 253
- Permeability in soils, 284
- Pilaster, 270, 426
- Piles, 143
- Pipe columns, 191
- Planning, structural, 384
- Plasticity of soils, 285
- Plastic:
 - hinge, 161
 - moment, 161
 - range, of ductile material, 161
 - section modulus, 161
 - stress behavior, 161
- Plastics, as structural materials, 20
- Platform pole construction, 122
- Plywood, 132
 - in built-up beams, 122
 - deck, 133
 - gusset, 150
 - horizontal diaphragm, 133, 353, 403
 - shear wall, 133, 353, 404
- Pneumatic structures, 35
- Point of inflection, 85
- Pole, wood, 122, 143
 - foundations for, 122
 - frame construction, 122
 - platform construction, 122
- Ponding, on roofs, 169, 389
- Porosity in soils, 284
- Portland cement, 207
- Post and beam structure, 25
- Power, 77
- Precast concrete, 206
- Pressure:
 - active, soil, 283, 308
 - design, for soil, 282
 - distribution in soil mass, 289
 - passive, soil, 283, 308
 - presumptive, in soil, 283
 - wind, 338
- Pressure wedge method, 97
- Presumptive soil pressure, 283
- Properties of:
 - forces, 41
 - geometric shapes of cross sections, 473
 - reinforcing bars, 209
 - structural lumber, 480
 - structural steel:
 - angles, 477, 478
 - channels, 476
 - pipe, 479
 - W shapes, 474
- Properties of sections (areas):
 - centroid, 468
 - moment of inertia, 60, 469
 - radius of gyration, 479
 - section modulus, 473, 479;
- Proportional limit, 63
- Punching shear, in footing, 253
- Radius of gyration, 479
- Rafters, 130
- Reactions, 15
- Reduction of live load, 389
- Reference design values for wood, 124
- Reinforced concrete, 205
- Reinforced masonry, 259
- Reinforcement:
 - anchorage of, 228
 - areas of, in slabs, 219
 - balanced, 213
 - bending of, 210
 - compressive, in beams, 218
 - concrete cover for, 210
 - development of, 228
 - grade of, 209
 - hook, 230
 - in masonry, 259
 - minimum, 209
 - properties of, 209
 - shrinkage, 210
 - spacing of, 210, 220
 - splice in, 231
 - temperature, 210
- Resistance factors,
 - for concrete, 210
 - general, 292
 - for steel, 159, 188
- Resolution of forces, 42
- Resonance of harmonic motion, 78
- Restoring moment, 340
- Restrained beam, 80
- Resultant, of forces, 43
- Retaining wall, 314
- Rigid frame, 104
 - approximate analysis, 111, 450
 - cantilever, 106
 - determinate, 106
 - general, 27, 105
 - indeterminate, 109, 450
 - for lateral force resistance, 319, 369
 - multistory, 450, 457
 - P-delta effect in, 99
 - sidesway, 109
 - single span bent, 110
- Rolled steel shapes, 156
- Roof:
 - cantilevered edges, steel framing, 185
 - deck, 132, 180
 - general requirements, 5
 - load, live, 389
 - plywood, 132
- Rotational buckling, 69
- Round columns, 143, 247
- Safe load tables for:
 - column footings, 254
 - concrete columns, 246
 - nails, 149
 - open web steel joists, 177
 - steel beams, 173
 - steel columns, 191
 - steel formed sheet decks, 181
 - wall footings, 256
 - wood columns, 143
- Safety, 1
- Sand, 287
- Sandwich panels, plywood, 122
- Section:
 - cut, 40
 - modulus, 61, 161, 473, 479
- Seismic (earthquake):
 - activity, 241
 - base:
 - isolation, 348
 - shear, 347
 - building code requirements, 344
 - effects related to building form, 343
 - isolation, 348
 - load, 345
 - mitigation, 348
 - separation joint, 347
 - site-structure interaction, 345
 - spectrum response, 343
- Separation joints, 347
- Service load, 390
- Settlement, of footings, 291
- Shallow bearing foundations, 248, 293, 409
- Shapes, rolled, steel, 156
- Shear:
 - center, 68
 - combined direct and shear stress, 68
 - development of, in beam, 66, 83, 84, 127, 167, 221
 - diagonal stresses, 65
 - diagram for beam, 84
 - double, 59
 - effects, 65
 - horizontal, 66
 - key, in retaining wall foundation, 314
 - on oblique cross section, 65
 - peripheral, 253
 - punching, 253
 - reinforcement in beams, 222
 - single, 59
 - stress, 58, 66

- Shear: (*continued*)
 vertical, 66
 wall, 354, 404
- Shear in:
 beams, 66, 84
 concrete, 221
 general, 84
 steel, 167
 wood, 127
 footings, 253, 257
- Shear reinforcement, 222
- Shear wall:
 anchorage, 356, 404
 concrete block, 269, 273, 405
 discontinuous, 332
 functions, 354
 interrupted, 332
 load capacity, 404
 load distribution to, 317, 403
 masonry (CMU), 269, 273, 405
 multistory, 405
 offset, 332
 overturn in, 340, 356, 404
 plywood, 133, 353, 404
 sliding of, 404
- Shelter function of construction, 3
- Shrinkage:
 of concrete, 209
 limit in soil, 286
 reinforcement for, 210
- Sidesway of rigid frame, 109
- Sill bolts for sliding resistance, 404
- Simple beam, 80
- Single shear, 80
- Site design, 281, 392
- SI units, xiii
- Slab and beam structure, concrete, 232, 392
- Slab, concrete:
 flat, 237
 framed on grade, 314, 398
 on grade (paving), 312
 one-way spanning, 233
 paving, 312
 reinforcement for, 219
 thickness, minimum, 221
 two-way spanning, 237
- Slenderness:
 of column, 93, 139
 ratio, 93
- Sliding:
 friction, 73
 of shear wall, 404
 on soil, 308
- Soft story, 327, 334
- Soil:
 Atterberg limits, 285
 classification, 288
 clay, 288
 cohesionless, 286
 cohesive, 286
 collapsing, 290
 conditions affecting construction, 282
 confinement, 289
 considerations affecting foundation
 design, 288
 design values for, 282, 292
 discovery of information, 291
 excavation in, 282
 expansive, 290
 fill, 281
 flocculent, 287
 friction in, 308
 grain size, 284
 honeycombed, 287
 investigation of, 282, 291
 liquid limit, 286
 particle size, 284
 penetration resistance, 293
 plasticity of, 285
 porosity of, 284
 pressure:
 active, 283, 308
 horizontal, 283, 308
 passive, 283, 308
 presumptive, 283
 vertical, 282, 288
 properties and identification, 283, 292
 sand, 287
 saturation, 284
 shrinkage limit, 286
 stability, 287
 stress in, 289
 structure, 286
 tests, 291
 void in, 283
 water content, 284
 weight, 283
- Solid-sawn wood, 114
- Solid structures, 22
- Solid wood columns, 139
- Space frame, two-way spanning truss, 458
- Spacing:
 of bars in concrete, 210, 220
 of stirrups in concrete beams, 222
- Specified compressive strength of concrete, 208
- Spectrum curves, seismic response, 343
- Spiral column, concrete, 240
- Splices in reinforcement, 231
- Stability:
 of beams, 82
 of columns, 94, 188
 in soils, 287
 of trusses, 104
- Stabilizing moment of building weight, 340
- Standard notation, xiii
- Standard penetration test (blow count, N),
 for soil, 293
- Standard shapes:
 steel, 156
 wood, 480
- Static equilibrium, 15, 42
- Steel:
 assembly process, 155
 angle, 157
 beam, 158
 bending in, 158
 bracing for buckling, 174
 concentrated load effects, 179
 deflection, 169
 end support conditions, 168
 lateral buckling, 166
 lateral unsupported length, 166
 nominal moment capacity, 163
 safe load table, 171
 shear in, 167
 torsional buckling, 167
 bolted connections, 196
 braced frame, 361
 built-up members, 187
 cable, 80
 cold-formed products, 179
 columns, 187
 bending factor, 194
 biaxial bending, 70, 193
 combined compression and bending, 95,
 145, 242
 connections, 195
 effective buckling length, 188
 framing for, 195
 lateral unbraced length, 187
 multistory, 435
 P-delta effect, 99
 relative slenderness, 187
 stability, 187
 connections, 196
 design values for, 156
 designation of structural products, 158
 floor deck, 179, 181
 formed sheet steel products, 180
 forming processes, 153
 framed beam connections, 200
 general concerns for, 19, 153
 inelastic stress behavior, 160
 joist, open web, 176, 405, 415, 435
 joist girder, 178, 415
 least-weight section, 166
 manufactured truss, 176
 open web joist, 176, 405, 415, 435
 pipe, 191
 planning framing systems, 184
 properties, 155
 reinforcement, 209
 rigid frame, 374, 440
 rolled shapes, 156
 roof deck, 179, 180
 standard products, 153
 strain hardening, 160
 system planning, 184
 truss, 176, 201, 408, 416
 usage considerations, 158
- Stirrups, 222
- Stone masonry, 276
- Strain:
 general definition, 56
 hardening, 160
- Strength:
 of concrete, 208
 design method, 2, 392
 yield, 63
- Stress,
 in beams, 82
 bearing, 128
 bending, 59
 combined, 68
 development of internal force, 56
 direct, 57
 flexural, 59
 kinds of, 17
 on an oblique section, 65
 shear, 58
 in soils, 289
 types of, 17
 yield, 63
- Stressed-skin panel, wood, 122

- Stress-strain:
 - definition, 17
 - diagram, 62
 - ductility, 62
 - modulus of elasticity, defined by, 62
 - proportional limit, 63
 - relationships, 62
 - yield stress, 63
- Structural:
 - computations, xi
 - design, 17
 - functions, 12
 - investigation, 18
 - lumber, 114
 - masonry, 262
 - materials, 18
 - safety, 1
- Structural systems, 21
 - attributes, 21
 - categorization, 22
 - types of:
 - arch, vault, and dome, 30
 - flatspan, 27
 - folded plate, 35
 - framed, 22
 - geodesic, 36
 - inflated, 35
 - lamella, 36
 - light wood frame, 117, 399
 - mast, 36
 - monopod, 38
 - pneumatic, 35
 - post and beam, 25
 - rigid frame, 27
 - shell, 35
 - solid, 22
 - space frame, 458
 - surface, 22, 33
 - suspension, 32, 90
 - tension, 32, 90
 - truss, 28
 - two-way spanning, 112, 237, 458
 - wall, 23
- Studs, wood, 144
- Subterranean building, 10
- Superimposed load, 54
- Surcharge effects in soils, 308
- Surface structures, 22, 33
- Suspension structures, 32, 90
- Symbols, xii
- Systems, structural, 21

- Tag-along technique, lateral bracing, 331
- T-beams, concrete, 216
- Tearing in bolted connection, 198
- Tees, steel, 156
- Temperature:
 - expansion, 63
 - reinforcement, 210
- Tension:
 - anchors, 150
 - structures, 32, 90
- Tension elements:
 - axially loaded, 88
 - cables, 32, 90
 - combined action in, 92
 - effective area in, 89
 - flexibility of, 90
 - net section in, 89
 - upset end, threaded rod, 89
- Thermal effects, 63
- Three-hinged structure, 31
- Three-sided building, 328
- Tied concrete column, 240
- Tiedown anchor, 356, 378, 404
- Timber:
 - connectors, 150
 - trusses, 135, 421
- Torsion:
 - accidental, 347
 - in beams, 69, 128
 - of buildings, 347
- Torsional buckling of beams, 69
- Torsional effect of lateral loads, 328
- Trussed bent, 437
- Trussed bracing for:
 - lateral forces, 362
 - steel frames, 367, 437
 - wood frames, 367
- Trusses, 28, 99
 - algebraic analysis, 51
 - bracing for, 104
 - connections, 134, 201
 - deflection, 102
 - delta, 202
 - forces in members, 47, 101
 - graphical analysis, 47
 - heavy timber, 135, 421
 - joints, method of, 47
 - loads on, 100
 - manufactured, 136, 176
 - Maxwell diagram, 47
 - method of joints, 47
 - notation of forces at a joint, 45, 47
 - open-web joists, 176, 405, 415, 435
 - roof, 408
 - steel, 126, 201, 408, 416
 - timber, 135, 421
 - two-way spanning, 458
 - types of, 135
 - wood, 134
 - zero stress member, 50
- Tubular steel columns, 192
- Two-way spanning structures, 112, 237, 458
 - concrete, 237
 - trusses, 458
- Ultimate strength design, 2
- Units of measurement, xiii
- Unsymmetrical bending, 70

- Vaults, 30
- Velocity, 76
 - of wind, 338
- Vertical:
 - diaphragm, 354
 - shear, 66
- Vibration, 77
- Void, in soils, 283

- Wall:
 - bearing, 5
 - with columns, 270, 476
 - curtain, 5
 - exterior, 5
 - footing for, 254
 - general functions of, 23
 - interior, 5
 - nonstructural, 5
 - partition, 5
 - retaining, 314
 - shear, 5, 354, 404
- Weak story, 327, 335, 337
- Web crippling in steel beam, 179
- Weight of building construction, 387
- Wide flange (W) shapes, 156
- Wind:
 - basic wind speed, 338, 339
 - building code requirements, 339
 - design wind pressure, 338
 - direct pressure on walls, 338
 - drift, 340
 - effects, 336
 - on buildings, 317
 - exposure condition, 339
 - load determination, 335, 401, 412
 - pressure, related to velocity, 335
 - simplified design for, 339
- Wood:
 - adjustment of design values, 125
 - beams, 126
 - bearing, 125, 128
 - board decks, 132
 - bolted joints, 147
 - built-up members, 122, 144
 - columns:
 - solid, 139
 - studs, 144
 - common wire nails, 147
 - composite members, 120
 - deck, 118, 132
 - defects, 116
 - deflection of beams, 128
 - density (weight), 116
 - design values, 124
 - diaphragm, 353, 403
 - dimension lumber, 118
 - duration of load, 125
 - engineered products, 119
 - floor joists, 130
 - general concerns, 19, 114
 - glued-laminated products, 119
 - grade, 118
 - hardwood, 114
 - heavy timber, 114, 136, 418
 - horizontal diaphragm, 353, 403
 - I-joists, 121
 - Joists, 130
 - laminated veneer lumber (LVL), 120
 - lateral support for beams, 128, 131
 - light frame construction, 117, 399, 410
 - load duration, 125
 - lumber, 114, 117, 480
 - metal framing devices, 150
 - modified design values, 125
 - modulus of elasticity, 126
 - moisture in, 117
 - nails, 147
 - nominal size, 117
 - oriented strand board (OSB), 121
 - parallel strand board (PSL), 120

Wood: *(continued)*

- plank deck, 132
- plywood, 132
- poles, 122, 143
- rafters, 130
- reference design values, 124
- repetitive use, 126
- seasoning, 116
- shear wall, 353, 404
- size factor for beam, 125, 127
- softwood, 114
- species, 114
- structural lumber, 114, 117, 480
- studs, 144
- trusses, 134, 418, 421
- use classification, 118
- weight (density), 116

Work, 77

- W shape, steel, 156, 474
- Wythe, masonry wall, 262

X-bracing, 362, 364

Yield point in ductile material, 63

Zero stress member, in truss, 50